



SAFETY DATA SHEET

Even Better Primer

Date of preparation: 2017-06-16

Version: 1

Reviewed on: -

Page 1 of 3

1. PRODUCT AND COMPANY INFORMATION

IDENTIFICATION OF THE SUBSTANCE/MIXTURE Even Better Primer

USE OF THE SUBSTANCE/MIXTURE Paint.

COMPANY IDENTIFICATION

Supplier: Fellert Acoustical Ceilings AB
Address: Kyrkängsgatan 6, 503 38 Borås, Sverige
Telephone: +46 (0)33-430 23 10
Fax: +46 (0)33-430 22 19
Contact: Mikael Nilsson
E-mail: www.fellert.com
Webpage: mikael@fellert.com

EMERGENCY TELEPHONE NUMBER

Swedish Poisons Information Centre 112 (acute), 010-456-67-00 (office hours)

2. HAZARDS IDENTIFICATION

GHS-US Classification

Not classified as hazardous under HCS 2012

GHS-US labeling

Hazard pictograms (GHS-US) : None required
Signal word (GHS-US) : None required
Hazard statements (GHS-US) : None required
Precautionary statements (GHS-US) : None required

OTHER HAZARDS

May dry out the skin at long-term/repeated exposure. May cause slight eye irritation. Vapors may irritate the respiratory tract.

The product does not meet the criteria for PBT (persistent / bioaccumulative / toxic) or vPvB (very persistent / very bioaccumulative).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Product does not contain any substances requiring to be declared under HCS 2012.

Other ingredients

Substance	CAS nr	%	Pictogram	H-phrases*	Category
2-Butoxy-1-ethanol**	111-76-2	1-5 %	GHS07 Warning	H302 H312 H315 H319 H332	Acute Tox. 4 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2 Acute Tox. 4
Xylene (mixture of isomers)**	1330-20-7	1-1,99 %	GHS02 GHS07 Warning	H226 H312 H315 H332	Flam. Liq. 3 Acute Tox. 4 Skin Irrit. 2 Acute Tox. 4

* For full wording of H-phrases see section 16.

**The substance has occupational exposure limit values, see Section 8



SAFETY DATA SHEET

Even Better Primer

Date of preparation: 2017-06-16

Version: 1

Reviewed on: -

Page 2 of 3

4. FIRST AID MEASURES

GENERAL RECOMMENDATION

Keep the victim warm and calm. Never give anything to eat or drink to an unconscious person. If uncertain or if symptoms remain, consult a doctor. Show this SDS to medical personnel.

INHALATION

Supply fresh air and rest. Consult a doctor if symptoms develop.

SKIN CONTACT

Remove contaminated clothing and shoes and wash before reuse. Wash skin with soap and water for several minutes. Consult a doctor if symptoms develop.

EYE CONTACT

Rinse opened eye for several minutes under running water (lukewarm). Keep eyelids apart. Remove contacts if present. Consult a doctor if any symptoms appear.

INGESTION

Rinse out mouth with water. Give two glasses of water to drink. Consult a doctor if symptoms develop.

5. FIREFIGHTING MEASURES

EXTINGUISHING MEDIA

May be combustible at high temperature. Use suitable extinguishing media such as Foam, Powder, Carbon Dioxide (CO₂) or Water Fog.

SPECIAL EXPOSURE HAZARDS

Combustion can produce irritating fumes such as carbon monoxide, carbon dioxide and other organic compounds. Do not breathe fumes.

SPECIAL PROTECTIVE EQUIPMENT AND ADVICE FOR FIRE FIGHTERS

Wear full protective equipment including breathing apparatus. Cool containers at risk with water and remove from fire when possible. Do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Ensure adequate ventilation. Do not breathe vapors. Avoid contact with skin and eyes. Use protective equipment according to section 8 of this SDS. Dust filter IIb (P2) may be required during sanding operations.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter sewers/surface or ground water. Inform the emergency services in case of spills.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Contain any spilled material by absorbing it in vermiculite, dry sand or earth and place into labeled containers for disposal (see Section 13). Small spills can be wiped up with paper. Irrigate contaminated area with plenty of water.

7. HANDLING AND STORAGE

HANDLING

Use personal protective equipment, see Section 8. Avoid contact with skin and eyes. Avoid breathing of fumes. Emergency eye wash should be available in the workplace. No food, drinks or smoking at the workplace. Remove all contaminated clothing. Wash hands and/or face before breaks and at the end of the workday.

STORAGE

Store in enclosed dry environment in original container at room temperature.



SAFETY DATA SHEET

Even Better Primer

Date of preparation: 2017-06-16

Version: 1

Reviewed on: -

Page 3 of 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

RECOMMENDED ENGINEERING CONTROLS

Ensure good ventilation. Wash basin and eye-wash station should be available in the working area.

CONTROL PARAMETERS:

2-Butoxy-1-ethanol:	8hr		15 min	
USA - NIOSH	5 mg/m ³	24 ppm	-	-
USA - OSHA	50 mg/m ³	240 ppm	-	-
Xylene (all isomers):	8hr		15 min	
USA - NIOSH	100 mg/m ³	435 ppm	150 mg/m ³	655 ppm
USA - OSHA	100 mg/m ³	435 ppm	-	-

MONITORING PROCEDURES

Not required.

INDIVIDUAL PROTECTION MEASURES

Always check applicability with your supplier of protective equipment. Use NIOSH approved equipment.

RESPIRATORY PROTECTION

Use only in well-ventilated areas. If ventilation is insufficient, wear respiratory equipment with , filter B and dust filter IIb (P2).

HAND PROTECTION

Normally not required.

EYE/FACE PROTECTION

Tightly fitting goggles if risk of splashes.

SKIN PROTECTION

Not normally necessary.

HYGIENE MEASURES

Wash thoroughly with soap and water after handling. Use barrier skin cream if skin irritation occurs. Check gloves regularly and after use. Replace if necessary (e.g. pinhole leaks).

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON FUNDAMENTAL PHYSICAL AND CHEMICAL PROPERTIES

(a) Appearance	Suspension
(b) Color	No information available
(c) Odor threshold	No information available
(d) pH	7 - 9
(e) Melting point/ freezing point	No information available
(f) Initial boiling point and boiling range	No information available
(g) Flash point	No information available
(h) Evaporation rate	No information available
(i) Flammability (gas, solid)	None
(j) Upper/lower flammability or explosive limits	No information available
(k) Vapour pressure	No information available
(l) Vapour density	No information available
(m) Relative density	1.22 kg/L
(n) Solubility(ies)	No information available
(o) Partition coefficient: n-octanol/water	No information available
(p) Auto-ignition temperature	No information available
(q) Decomposition temperature	No information available
(r) Viscosity	No information available



SAFETY DATA SHEET

Even Better Primer

Date of preparation: 2017-06-16

Version: 1

Reviewed on: -

Page 4 of 4

(s) Explosive properties	None
(t) Oxidising properties	None
(u) VOC	Max 85,4 g/l, Max 0,71 lbs/US Gallon

Note: These are typical values and do not constitute a specification.

10. STABILITY AND REACTIVITY

STABILITY

Stable product under normal conditions of handling and storage.

CONDITIONS TO AVOID

Not known under normal conditions of handling and storage.

MATERIALS TO AVOID

Strong acids, bases and alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS

Fumes containing oxides of carbon can develop in case of fire.

11. TOXICOLOGICAL INFORMATION

Test data: No data available on product.

EXPOSURE HAZARDS

	ACUTE EFFECTS	CHRONIC EFFECTS
SKIN CONTACT	May dry out the skin at long-term/repeated exposure.	-
EYE CONTACT	May cause slight eye irritation.	-
INHALATION	Vapors may irritate the respiratory tract.	-
INGESTION	-	-

OTHER INFORMATION

Ethylglycol ethers have been demonstrated to induce birth defects as well as disturbances of the sperm production at relatively low levels.

The critical effects of occupational exposure to xylene are assessed to be irritation and effects on the central nervous system (CNS). Increased symptoms of irritation and CNS effects have been reported for exposures to 50 ppm m-xylene. More pronounced irritation of the eyes, nose and throat have been reported after short exposures to 200 ppm. In studies in man it has been shown that exposures to 90 ppm xylene causes decreased performance in neuropsychological tests. Exposure to 70 ppm did not affect the performance in similar tests.

Impaired memory and concentration, depression and tiredness can appear after prolonged and/or high-level exposures to xylene in combination with other solvents. Animal studies support the conclusion that chronic effects on the CNS appear at 100-200 ppm.

Effects on the development of the nervous system has been demonstrated in pups to rats exposed to 200 ppm technical grade xylene during pregnancy.

Skin contact with liquid xylene caused redness and a sense of burning and pricking in the skin. Repeated skin contact leads to defatting and skin irritation. Skin exposure to liquid xylene can affect the internal organs.

12. ECOLOGICAL INFORMATION

AQUATIC TOXICITY

No data on product. Not classified as hazardous for the environment based on data for ingredients.

PERSISTENCE AND DEGRADABILITY

No data available.

BIOACCUMULATIVE POTENTIAL

No data available.

MOBILITY IN SOIL

No data available.



SAFETY DATA SHEET

Even Better Primer

Date of preparation: 2017-06-16

Version: 1

Reviewed on: -

Page 5 of 5

SUMMARY

The product is not classified as an environmental hazard. However, do not allow the product to reach ground water, water course or sewage system.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

14. TRANSPORT INFORMATION

Not classified as dangerous goods in accordance with DOT/ADR/RID/IMO/IATA/ICAO.

15. REGULATORY INFORMATION

Inventory Status

TSCA To the best of our knowledge all ingredients of this product are listed unless specifically exempted.

EU All ingredients of this product are listed in EINECS or ELINCS, unless specifically exempted under EU Directive 67/548/EEC (as amended).

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions, which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Hazardous Material Information (HMIS)		National Fire Protection Association (NFPA)	
Health	0	0	Health
Fire	1	1	Fire
Reactivity	0	0	Instability

Health	4 Deadly	3 Extreme Danger	2 Dangerous	1 Slight hazard	0 No hazard
Fire	4 < 73 °F	3 < 100 °F	2 < 200 °F	1 >200 °F	0 Will not burn
Reactivity/ Instability	4 – May detonate	3 Explosive	2 Unstable	1 Normally stable	0 Stable

H PHRASES GIVEN UNDER SECTION 3 IN PLAIN TEXT

H226 Flammable liquid and vapour
H302 Harmful if swallowed
H312 Harmful in contact with skin.
H315 Causes skin irritation
H319 Causes serious eye irritation
H332 Harmful if inhaled



SAFETY DATA SHEET

Even Better Primer

Date of preparation: 2017-06-16

Version: 1

Reviewed on: -

Page 6 of 6

Version number 1
Date prepared 16th June 2017
Supersedes Version None
Nature of revision First issue under HSC 2012.

Based on HSC 2012 and EU Regulation 1907/2006

The current Safety Data Sheet was defined by Fellert Acoustical Ceilings AB on the basis of knowledge of the product at the date of issue.

It is the duty of the user:

- to develop under his own responsibility, the safety dispositions regarding the use of the product taking into account the data from this sheet.
- to pass to all users and operators the appropriate safety data and warning regarding the risks mentioned in the documentation relative to the utilization of the product.
- to be aware of possible risks faced when the product is used for other uses than those for which it has been designed.

This SDS has been compiled with assistance from Amasis Konsult AB, Solna, Sweden.

End of Document. Number of pages = 6